

GTS Handling Devices

Various Glass Handling & Carrying Devices

January 2016

Glass Handling Equipment

Double Handle Glass Carrying Device

Glass carrying device with rubber-lined area of 200mm x 80mm and clamping range of up to 40mm.

Loading Capacity : 160kg

Dimensions : 200mm x 88mm x 175mm

GTS/WH-9602MA



Single Handle Glass Carrying Device

Glass carrying device with rubber-lined area of 200mm x 80mm and clamping range of up to 25mm.

Loading Capacity : 80kg

Dimensions : 200mm x 88mm x 175mm

GTS/WH-9602MS



60mm Adjustable Angle Suction Clamps

A double suction lifter adjustable between 60° and 240° to secure glass panels in place during UV bonding - NOT for carrying.

Key Features and Benefits

- Holds glass sheets on either inside or outside surface
- Height and position can be adjusted by up to 8mm using the knobs located on each arm
- 60mm rubber suction pads hold glass panels firmly in place until they are bonded

TOOLS/UV2933



Roller Blocks

High-density polyethylene roller blocks for tilting large heavy sheets of glass 90° vertically. The wide pocket accepts thick glass, insulating glass and doors with patch fittings.

Key Features and Benefits

- Rotate and support heavy sheet or insulated glass with ease, rubber pads prevent slippage and provide traction for tilting
- Loading capacity of 181kg per block

TOOLS/RB200



117mm Angle Suction Cup

A double suction cup connected by a rotatable link, adjustable between 45° and 300° for application to glass during construction - NOT for carrying.

Key Features and Benefits

- Spare handles, springs and pads available
- Supplied with protective covers on pads

Loading Capacity : n/a

Diameter : 117mm

GTS/WH-9602G



Glass Hand Lifting Sling

A strong, heavy duty glass lifting sling made from leather. Each sling is approximately 1 metre from handle to handle.

Key Features and Benefits

- Thick felt lining to support the glass
- Hardwood handles
- Loading capacity of 80kg

TOOLS/0508

